



RAZON ENGINEERING COMPANY PRIVATE LIMITED

660, Taboot Street, P.O.Box No.49, PUNE-411001 [India] Ph:+91-20-26130791, 26132217
Telefax: +91-20 26130017 E-mail: razonengg@gmail.com, Website: www.razonengg.com

AN ISO 9001-2008 COMPANY READY PLASTER AND PUTTY

Ready Plaster & Putty are two products, factory prepared ready to use plaster and putty, comprising of carefully selected raw material, high adhesive polymeric ingredients to give high bond strength, high adhesion, tough, scratch resistant excellent finish waterproof plaster and putty. Ready Putty is most useful for repairs and make jobs and for use as fine putty before painting.

With the quantum of plaster work, increasing rapidly, to maintain consistent quality of plaster is stressful and slightly tedious by conventional methods. Hence, READY PLASTER AND PUTTY is developed to make sure, you have consistent quality plaster at your sites.

Making up plaster, repairing plaster, external or internal requires skill, and correct materials. Due to high slit and very high fines sand, plaster quality is poor, also large number of cracks appear in the plastered surface. Also rebound in plaster is very high, due to which the mason is unhappy, and cannot give a good finish. Ready Plaster & Putty does away with all these handicaps, it is easy to use, a mason can be easy apply Ready Plaster & Putty using conventional tools such as “thapi” or latest technology spray plaster machines. It has good workability, good finish, and comes in ready to use packs, Ready Plaster & Putty is merely added to water at site and used for plastering or for good finish waterproof putty prior to painting.

Clean the surface which is to receive Ready Plaster & Putty thoroughly with wire brush, use Razon XRG for cleaning if required, moisten the surface. Add Ready Plaster & Putty to water (generally 30% - 40% water is use to obtain plaster mortar workable consistency) use sufficient quantity of water to obtain mortar of uniform consistency. Use this mortar/paste to plaster as usual. Ready Plaster & Putty can be applied using “palti patra ” or “patra -Thapi” till smooth layer plaster is obtained.

NO	PRODUCT DATA	
1	Colour	Whitish Grey
2	Principle constitution	Cementation, coarse inert particles, factory prepared high resin high polymer ready to use waterproof plaster.
3	Specific Gravity	2.5
4	Storage Life	6 months if kept in hermetically sealed bags as supplied.
5	pot Life	<1 hours.
6	Toxicity	Nil
7	precautions	Clear surface thoroughly clean surface with Razon XRG for old surface make up or plastering.
8	Curing	Depending on the ambient conditions, and humidity curing may be done as regular.
9	Method	Use 30-40% water. add ready plaster to water, add slowly. Stir continuously whilst mixing to obtain mortar of desired consistency. If use internally/externally cure 2-3 time daily for 7 days.
10	Packing	5 Kg, 20 kg, hermetically sealed polythelene double bags.

It is strongly recommended that site trials be conducted using site conditions and available raw materials to evaluate the product. Since site materials and conditions are beyond our control and since above suggestions and recommendations are based on our site trials and laboratory product evaluation & trials, and since methods of use at site are beyond our control. Hence, no guarantee can either be implied or enforceable

OTHER PRODUCTS

Coatings: Rubberised Instant Waterproof Coating • White Water Proofer • Polyurethane Coating - GHF 111 • Triple Layer Polyurethane Waterproof/ Thermal Coating • Primer Coat PU SG 104 • Top Coat PU ALK – 104 • Silver Coat PU 104 • Clear PU Lacquer (gloss) • Clear PU Lacquer (matt) • Coal Tar Epoxy CTE – 110 • Coal Tar Epoxy EP-10 • Epoxy Coating EC-111 • Primer Epoxy Coating PR 111 • Silver Coating SC 203 • Epoxy Floor Coating G-78 AND M-86 • Damp Proofer • Bitumenous Japan Paint 151 • Supreme Waterproof Cement Paint ARCEM –101 • Premium Waterproof Cement Paint ARCEM –119 • Royal Waterproof Cement Paint ARCEM 1100 • Green Chromo Oxide Epoxy Primer •

Admixture: SPRMC 808 S11 B • Super Plasticizer –IWSP (M) – 101 • Super Plasticizer –IWSP (N) – 103 • Accelerator –2080 • Integral Water Proofer • IWSP –102 • I.W.P. Powder • Intrair (A.E.A) 120N • Master Plaster MP CS 101 • Block Maker BM-10 • Rapid Grout RG –117 • Tile Master TM – 1 • Anchorex 428 • Floor Hardner • Hycrete RJ – 608 • Brick Master • Super Paver • Pipe Master • Toughcrete P109 • Guniting Admixture GS-942 • Non Shrink Grout Admixture NSG A-II

Other Products : Tile Fix # 1 • Tile Fix # 1A • Tile Fix SP # 1 • Strextra NSG 110 •

Strextra - NSG 2024 • Easy Grout • Water Repellent WBWR – 2023 •

Water Repellent SBWR – 5000 • Shutter Coat for Wood & Metal •

Concrete Cure Coating – 111 • Concrete Cure Coating – 103 •

P.A. Bound • P.A. Mortar TH – 4 • PA. Mortar EF – 1 • P.A. Mortar

Slurry • Marble Fix • Floor Repair Mortar • Insta Plugging Mortar •

Pipe Joint Sealer • Tile Joint Sealer • Metal Protect • RZ – Polymer

ED Mortar • Special Grouting System • Anti Hack Paint (XRG) •

Tuffar • ADMGP – 1 • P A – Resin 651XXX • Hak Safe AL 111 •

Paint Remover PR – 128 • COLGROUT Admixture CG – 101S •

Rock Splitting Grout ATC-A201 • Ready Plaster • Best Plaster Putty



It is strongly recommended that site trials be conducted using site conditions and available raw materials to evaluate the product. Since site materials and conditions are beyond our control and since above suggestions and recommendations are based on our site trials and laboratory product evaluation & trials, and since methods of use at site are beyond our control. Hence, no guarantee can either be implied or enforceable