



RAZON ENGINEERING COMPANY PRIVATE LIMITED

660, Taboot Street, P.O.Box No.49, PUNE-411001 [India] Ph:26130791, Telefax: 26130017

E-mail: razonengg@gmail.com, Website: www.razonengg.com

AN ISO 9001-2008 COMPANY TILE JOINT SEALER

Tile Joint Sealer is a cementitious formulation for sealing tile-joints or tile-sandhas. Tile joints are conventionally sealed by using white cement. These joints are seldom cured. Tile Joint Sealer is a factory prepared formulation, which does not require curing; it sets into a hard filler on its own within 24 hours. Cement tends to shrink on setting thus getting loose in joints. Tile Joint Sealer expands on setting hence seals the joint/sandhas completely.

Loose tile-joints or tile-sandhas, or open tile joints can cause seepage. It is very important to have high adhesive and high bond strength Tile Joint Sealer. Tile Joint Sealer has very high adhesive strength and high bond strength, both features necessary for tile joint sealing.

To seal tile-joints or tile-sandhas in old tiles, clean the tile joints or sandhas well using thin brush, and a 'Palti pata' to remove all loose material between the joints.

Mix water with Tile Joint Sealer to bring it to paste like consistency, press this mortar into the joints with fingers, press firmly, clear excess material using clean cloth. Allow 24 hours for Tile Joint Sealer to harden. Preferably cure for 2-3 days.

Tile Joint Sealer can be used for ceramic tiles, glazed tiles, marbles slabs, granite tiles / slabs for external facades, in bathroom, W.C., swimming pools, basements, hospitals, hotels, kitchen etc.

Tile Joint Sealer is available in following standard colours Pink, Green, Majenta, White, Blue, Pacific-Blue, Alpine-Blue, Bottle green, Sapphire, Black, Ivory, Burgundy.

(Other shades on request)

No	PRODUCT - DATA	
1	Consistency	Powder.
2	Colours	Standard colours.
3	Packing	½ kgs.
4	Shelf life	6 months – 1 year.
5	Pot life	1 – 2 hours after mixing.
6	Application	Sealing old Tile joints or sandhas sealing in freshly laid tiles etc. In case of leaking sunken portion exhibiting seepage. Clean all Tile Joints & seal Tile joints. Plug cavities if any at door frame embedded into the floor with Tile Joint Sealer, use trowel if necessary to plug this cavity completely.
7	Coverage	400 sq.ft.per ½ kg for 1'X1' tiles.
8	Storage	Store in dry place. Avoid packets from tearing.